



TECHNICAL SPECIFICATIONS

CMW.1000 BASIC PELLET BLASTER Straight 3mm Pellet Blast Cleaning

Description

- Frame construction, ice hold and all panels in V2a stainless steel, ice hold lid in acrylic glass.
- All functions and controls pneumatic
- Source pressure manometer **0 > 16 bar - 0 > 230 psi**
- Nozzle work pressure manometer **0 > 16 bar - 0 > 230 psi**
- Ice rate / grinder manometer **0 > 16 bar - 0 > 230 psi**
- Work pressure regulator **2 > 15 bar - 30 > 218 psi**
- Ice rate /grinder regulator **1 > 4 bar - 15 > 60 psi**
- Unit is mounted on two rubber wheels
- Dry ice storage hold **50 kg / 110 lbs**
- CE CERTIFIED to EU Standards

System Package includes

- **CMW.1000 Blasting Unit**
- **Blast Gun Set, incl. 4x Venturis, 4x Aluminum Barrels (S-M-L Airflow),**
- **2x Flat Nozzles, 45° bent- and short straight barrels**
- **Standard 5m/16.5ft blast hose assembly.**
- **Standard 5m/16.5ft earth ground wire.**
- **Detachable Side Grip**
- **Tools**

Specifications

- **Dimensions** **H 102cm / 40¼" x W 36cm / 14¼" x D 53cm / 20¾"**
- **Net Weight** **56 kg / 123 lbs**
- **Certified maximum pressure** **15 bar / 218 psi**
- **Blast Gun air volume range** **0.8 m³–12 m³ p/min. / 30–420 cfm**

CMW CO2 TECHNOLOGIES

CALL +91.22.2651.0929 FAX +91.22.2651.8594 EMAIL sales@cmw-dryice.com